

HPE Aruba Networking 730 Series Campus Access Points

HPE Aruba Networking AP-735 (RW) Tri Radio 2x2 Wi-Fi 7 Internal Antennas Campus Access Point (S1G42A)



What's new

- Wi-Fi 7 access points ideal for enterprises, healthcare, LPV, education, retail, and industrial IoT deployments.
- Comprehensive triband coverage across 2.4 GHz, 5 GHz, and 6 GHz delivers up to 9.3 Gbps maximum aggregate data rate.
- Patented Ultra Tri-band (UTB) filtering improves the use of 5 GHz and 6 GHz bands.

Overview

The HPE Aruba Networking 730 Series Campus Access Points go beyond the Wi-Fi 7 standard to improve wireless performance, strengthen network security, deliver precise location-based services, and act as a secure IoT platform, enabling enterprises to increase the value of their wireless investment and unlock operational efficiencies.

The 730 Series includes unique Ultra Tri-band (UTB) filtering and dual 5 Gbps Ethernet ports to remove coverage gaps, provide greater resiliency, and deliver fast connectivity with enhanced security. HPE Aruba Networking Central provides intelligent automation, AI insights, and unified infrastructure management to help drive efficient IT operations.



- High density IoT support with two integrated Bluetooth 5.4 and 802.15.4 radios for Zigbee support and two USB port extensions.
- Built-in GNSS receiver, barometric pressure sensor, and intelligent software enable Access Points to self locate and act as reference points for accurate indoor location measurements.
- High availability with dual 5 Gbps ports for redundant Ethernet and power.

The 730 Series include a limited lifetime warranty.

Features

High Performance Wi-Fi 7

The HPE Aruba Networking 730 Series Campus Access Points are based on the IEEE 802.11be standard and designed to take advantage of the 6 GHz band through three dedicated radios, which translates into far greater speeds, wider channels for multi-gigabit traffic, and less interference.

This access point series delivers up to 9.3 Gbps maximum tri-band aggregate data rate by using three 2x2 MIMO radios (2.4 GHz, 5 GHz, and 6 GHz), and achieve capability of up to 14.4 Gbps maximum aggregate data rate using optional dual 5 GHz and 6 GHz radio modes.

Patented Ultra Tri-band filtering enables enterprises to take advantage of the high end of 5 GHz with the lower end of 6 GHz without creating coverage gaps or islands.

Enhanced wireless experience with HPE Aruba Networking ClientMatch technology that removes sticky client issues by steering a client to the AP where it receives the best radio signal.

High availability with two HPE Smart Rate Ethernet ports for hitless failover for both data and power. Configurable to 1, 2.5, or 5 Gbps (or 100 Mbps), these dual ports provide business continuity for mission-critical applications.

Simplified Access with Enhanced Security

The HPE Aruba Networking 730 Series Campus Access Points offer enhanced security with Dynamic Segmentation to remove the time-consuming and errorprone task of managing complex and static VLANs, ACLs, and subnets by dynamically assigning policies and keeping traffic secure and separated.

MACsec-capable 5 GbE port extends wired Ethernet protection to the access point.

This access point series offers stronger encryption and authentication with WPA3, secure credentials/keys storage for guest access with Enhanced Open, and user and IoT access policy enforcement firewalls (PEF).

The access points simplify policy enforcement using the HPE Aruba Networking Policy Enforcement Firewall (PEF) to encapsulate traffic from the access point to the gateway (or mobility controller) for end-to-end encryption and inspection.

For enhanced device assurance, HPE Aruba Networking 730 Series Campus Access Points include an installed TPM for secure storage of credentials, keys, and boot code.

AP as an IoT platform

The HPE Aruba Networking 730 Series Campus Access Points can serve as flexible IoT platforms that bolster network security and provide coverage for a broad range of IoT devices, without the need for network overlays.

This access point series provides two built-in Bluetooth 5.4 and 802.15.4 radios for Zigbee support to simplify deploying and managing IoT-based location services, asset tracking services, security solutions and IoT sensors. Two USB port extensions provide connectivity to a range of IoT devices.

Advanced IoT Coexistence (AIC) feature uses built-in filtering to allow Wi-Fi and Bluetooth Low Energy (BLE)/Zigbee radios to operate at maximum capacity without the impact of interference.

HPE Aruba Networking Central IoT Operations unifies visibility of IT and OT infrastructure within the network health dashboard by extending network monitoring and insights to BLE, Zigbee, and other non-IP IoT devices to help non-Wi-Fi device onboarding and data collection.

HPE Aruba Networking Central Client Insights uses deep packet inspection to provide additional context and behavioral information that helps verify devices are receiving proper policy enforcement and continuously monitors for rogue devices.



Page 3

Energy Saving and Self-locating Access Points

The HPE Aruba Networking 730 Series Campus Access Points help organizations reduce energy consumption and deliver precision indoor location services with the Access Points that serve as reference points for client devices and other technologies using fine time measurement.

This access point series offers precision locationing with support of FTM 802.11az for sub-1 meter accuracy and built-in GNSS receiver for high accuracy indoor location measurements.

Built-in barometric sensor for altitude locationing within multi-story buildings provides floor-level mappings.

Al-powered dynamic power save mode enables the HPE Aruba Networking 730 Series Campus Access Points to automatically wake up at a schedule when connectivity demand arises, reducing power demands and lowering the energy footprint to align with the organization's sustainability initiatives.

The target wake time (TWT) establishes a schedule for clients to communicate with an Access Point to help improve client power savings and reduce airtime contention. Intelligent Power Monitoring provides energy consumption insights as APs continuously monitor and report hardware energy usage.

Technical specifications

HPE Aruba Networking AP-735 (RW) Tri Radio 2x2 Wi-Fi 7 Internal Antennas Campus Access Point

Product Number	S1G42A
Differentiator	Available everywhere except, US, Israel, Egypt and Japan
Certifications	Bluetooth SIG; Ethernet Alliance (PoE, PD device, Class 5); UL2043 plenum rating; Wi-Fi Alliance (WFA): Wi-Fi CERTIFIED a, b, g, n, ac, 6, 7 WPA, WPA2 and WPA3 Enterprise with CNSA option Personal (SAE), Enhanced Open (OWE) WMM, WMM-PS, W-Fi Agile Multiband
Input voltage	PoE-PD: 48Vdc (nominal) 802.3at/bt PoE (Class 4 or higher); DC power interface: 12 VDC(nominal, +/- 5%), accepts 2.1mm/5.5mm center-positive circular plug with 9.5mm length
Regulatory	FCC/ISED CE Marked RED Directive 2014/53/EU EMC Directive 2014/30/EU Low Voltage Directive 2014/35/EU UL/IEC/EN 60950 IEC/EN 62368-1 EN 60601-1-1, EN60601-1-2
Wi-Fi antenna	Integrated down-tilt omni-directional antennas for 2x2 MIMO with peak antenna gain of 5.1dBi in 2.4 GHz, 5.5dBi in 5 GHz (5.2dBi in dual-5 GHz mode) and 5.3dBi in 6 GHz (5.2dBi in dual-6 GHz mode). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP
	The downtilt angle for maximum gain is roughly 30 to 40 degrees.
Connectivity, standard	Wi-Fi 7 (IEEE 802.11be)
Ports	E0, E1: Two Ethernet wired network ports (RJ-45); U0, U1: Two USB 2.0 host interface (Type A connector); Kensington security slot; Serial console interface (proprietary, micro-B USB physical jack); Reset button: Factory reset, LED mode control (normal/off); Visual indicators (four multi-color LEDs) for System (1x) and Radio (3x) status
Mounting	A mounting bracket has been preinstalled on the back of the AP. This bracket is used to secure the AP to any of the mount kits (sold separately). Optional mounting kits available, see the ordering guide.
Power consumption	Maximum (worst case) power consumption (without/with USB devices attached): DC powered: 20W/31W. PoE powered: 24W/36W. Notes: This assumes that up to 10W is supplied to the attached USB device(s). Maximum (worst-case) power consumption in idle mode: 8W/19W (DC) or 12W/24W (PoE). Maximum (worst-case) power consumption in deep-sleep mode: 1.5W (DC) or 2.0W (PoE).
Radio coverage	AP type: Indoor, tri radio, 2.4 GHz, 5 GHz and 6 GHz (concurrent) 802.11be 2x2 MIMO
Warranty	Limited lifetime warranty. See the warranty duration.

Bluetooth is a trademark owned by its proprietor and used by Hewlett Packard Enterprise under license. All thirdparty marks are property of their respective owners.

For additional technical information, available models and options, please reference the QuickSpecs

HPE Aruba Networking Services

HPE Aruba Networking services simplify and accelerate the network technology lifecycle, enabling your network to scale with better predictability and cost-effectiveness. Whether you operate your own network and need to improve your IT efficiencies, or you want to offload some of the burden, we have the services you need to reach your goals.

Learn more about what HPE Services -Aruba Networking has to offer at: https://www.hpe.com/edge/services

Support Services

Our support portfolio provides the essential support elements as well as proactive and preventive features to help you improve your team's productivity and get the most from your network. Our support customers benefit from faster issue resolution, simplified operations and efficiencies, and reduced network issues.

Professional Services

With deep intellectual capital and purpose-built tools, our team delivers a range of standard and custom professional services designed to accelerate your value from HPE Aruba Networking technology.

Project based services include: Annual subscription services include:

- Planning, audit, and assessment
 Network optimization
 - Architecture review and design Intelligent Operations
- Deployment, migration, and knowledge transfer
- Customer Experience Management

Visit HPE.com

Our Education Services allow your team to come up to speed quickly.

HPE GreenLake for Networking

Our NaaS solution, is part of the HPE GreenLake services family, and simplifies network operations, accelerates equipment handling, and increases the value of your HPE Aruba Networking solution. If you need expert guidance and automation-based operations for your team, please explore our NaaS approach through HPE GreenLake for Networking.

Contact us

Hewlett Packard

Enterprise

Make the right purchase decision. Contact our presales specialists.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Image may differ from the actual product PSN1014839280CZEN, June, 2025.

[©] Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.